

CLAIMS

1. A door, comprising:

a door frame;

a door leaf that swings on hinges in said door frame, with a front and a rear cover panel with at least one transducer device mounted therein, wherein said door leaf acts as a loudspeaker and includes a stiff, light structural part that maintains fed-in vibrational energy and by flexural waves propagates this energy in at least one active surface perpendicular to its thickness to distribute resonance mode vibration components over at least one surface, which has specified, preferred locations or sites within it for transducer devices, which are entirely and exclusively affixed on the structural part at one of the locations or sites to set the structural part into vibration and to allow it to resonate, thus creating an acoustic radiator that delivers an acoustic output signal when it vibrates in resonance, the front and/or the rear cover panel of the door leaf being part of the stiff, light structural component.

2. The door of claim 1, wherein the signals are conducted from said door frame to said door leaf over at least one hinge.

3. The door of claim 2, wherein a switching element interrupts the conduction of signal when the door is open.

4. The door of claim 1, wherein corresponding contacts for signal conduction are situated on said door leaf and on said frame associated therewith.

1

1 5. The door of claim 1, further comprising a flexible, damping support element situated
2 between said front and rear cover panels.

1

1 6. The door of claim 5, wherein said transducers include electrodynamic inertial vibration
2 drivers.

1

1 7. The door of claim 6, wherein said front and rear cover panels each have a surface that
2 comprises criss-cross veneer.

1

1 8. The door of claim 1, wherein said door leaf has at least one bass reflex opening.

1

1 9. The door of claim 1, wherein said front cover panel is equipped with a clamping device that
2 maintains the stiff, light structural part of the front and/or rear cover panel under an adjustable
3 amount of tension.

1

1 10. A door leaf that receives an electrical acoustic signal, comprising:

2 front and rear parallel cover panels that sandwich an acoustic sandwich core that includes a
3 recess within which a transducer that receives an input signal indicative of the electrical acoustic
4 signal is mounted, said transducer emits an audio signal that excites said front cover panel and said
5 acoustic sandwich core such that said front cover panel and said acoustic sandwich core provide a
6 multimodal resonance radiator that delivers an acoustic output signal to the area adjacent to said

7 front cover panel.

1

1 11. The door leaf of claim 10, wherein said transducer comprises an electrodynamic inertial
2 vibration driver.

1

1 12. The door leaf of claim 10, wherein said transducer comprises a piezoelectric driver.

1

1 13. The door leaf of claim 10, wherein said acoustic sandwich core comprises a nomex
2 honeycomb structure.

1

14. The door leaf of claim 10, wherein said acoustic sandwich core comprises an aluminum
honeycomb structure.

1

15. The door leaf of claim 10, wherein said acoustic sandwich core comprises a high resistance
foam.

1

16. The door leaf of claim 10, further comprising a second transducer mounted in a second
2 recess between said front and rear parallel cover panels, wherein said second transducer is orientated
3 to drive said rear parallel cover panel to resonance in order to deliver a rearward launched acoustic
4 output wave, and said first and second transducers are separated by a flexible damping support
5 element.

1

Sub 97
1 17. The door leaf of claim 11, further comprising an adjustable clamping device that controls the
2 amount of tension in the region of said acoustic sandwich core to selectively change the acoustic
3 properties of said front cover and said acoustic sandwich core.

1
1 18. The door leaf of claim 17, wherein said front cover and said rear cover include multi-layer
2 pinewood veneer.

1
1 19. A door leaf that receives an electrical acoustic signal, comprising:
2 an acoustic core separated by front and rear parallel cover panels, wherein said acoustic core
3 includes a recess within which a first transducer is mounted that receives an input signal indicative
4 of the electrical acoustic signal, said first transducer emits an audio signal that excites said front
5 cover panel and said acoustic core such that said front cover panel and said acoustic sandwich core
6 provide a multimodal resonance radiator that delivers an acoustic output signal to the area adjacent
7 to said front cover panel.

add
a8